

The BS-678BT, of which cabinet is made of wood, can be installed in a vertical or horizontal orientation. Either concealed in-wall wiring or exposed wiring can be used for speaker cable connection. The speaker structure that permits direct wall-mounting with screws prevents the speaker from falling easily even if an outward force is applied to. The input impedance can be easily changed by changing the tap position of the transformer. Two built-in 6-inch double cone speaker units deliver high quality sound. The push-in type input connector makes cable connections easy and allows bridge wiring. BS-678BT have a built-in attenuator and can be connected to a 2-wire or 3-wire system.



Order no: BS-678BT

Specifications

Frequency response	150 Hz - 20 kHz
Connection	Push-in connector (bring terminal)
Sensitivity (1#V, 1#n) (combined)	94 dB
Speaker component	16 cm double cone-type
Rated input	6 W, 3 W
Tappings	6 / 3 / 1.5 / 0.8 W (100 V), 3 / 1.5 / 0.8 / 0.4 W (100 V)
Rated impedance	70 V, 100 V
Weight	1,7 kg
Certificates	Ease
Dimensions (W x H x D)	250 x 190 x 110 mm
Dimensions (ø x D)	x 110 mm
Gross weight	2 kg
Finish	MDF, black (RAL 9011 or equivalent)
Operating temperature	-10°C to +50°C

Appearance

