



EN 54 Certified Speakers

## F-2000BTWP EB-Q SPEAKER

3 different versions available: Low impedance, high impedance and weatherproof version  
2-way speaker with high quality 10 cm woofer and balanced dome tweeter  
Octagonal horn for clear, wide-area sound coverage  
Great variety of brackets available  
Easy impedance selection by rotary switch  
Built-in speaker protection for low impedance models  
Certified according to EN 54-24

---



Order no: F-2000BTWP EB-Q  
Alternative products: VX-3008F, VX-3004F,  
VX-3016F, SX-2000SM, VX-2000,  
VM-3360VA, VM-3240VA, VM-3240E,  
VM-3360E, VP-3504, VP-3154, VP-3304,  
VP-2421, VP-2421incl, VP-2241, VP-2241incl,  
VP-2122incl, VP-2122, VP-2064, VP-2064incl

---



# F-2000BTWP EB-Q

## SPEAKER

### Specifications

Frequency response	65 Hz - 20 kHz
Connection	Screw terminal
Sensitivity (1#V, 1#m) (combined)	92 dB
Speaker component	Woofer: 20 cm cone-type Tweeter: 25 mm dome-type
Directivity angle horizontal	110 °
Directivity angle vertical	100 °
Rated input	60 W
Tappings	100 V (60 / 30 / 15 / 3 W), 70 V (60 / 30 / 15 / 7.5 / 1.5 W)
Rated impedance	100 V, 70 V, 8 Ω
Crossover frequency	2500 Hz
Weight	7,4 kg
Certificates	EN 54-24, IPX4
Dimensions (W x H x D)	244 x 373 x 235 mm
Dimensions (ø x D)	x 235 mm
Gross weight	9,2 kg
Finish	HIPS resin, Steel plate, black (RAL 9011 or equivalent)
Operating temperature	-10°C to + 50°C

# F-2000BTWP EB-Q

SPEAKER

Appearance

